

Safety Data Sheet

Prepared in Accordance with HCS 29
C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

- | | | | |
|--|---|-------------------------|------------|
| 1.1 Product Identifier | 3229B0 | Revision Date: | 03/13/2024 |
| Product Name: | STONSET FP9 RESIN | Supersedes Date: | 01/06/2023 |
| 1.2 Relevant identified uses of the substance or mixture and uses advised against | Base component of 2 components coating - Industrial use. Advised against: others than recommended | | |
| 1.3 Details of the supplier of the safety data sheet | | | |
| Manufacturer: | Stonhard, Division of StonCor Group, Inc.
1000 East Park Avenue
Maple Shade, NJ 08052

+1 856 7797500 (US) | | |
| Datasheet Produced by: | ehs@stonhard.com | | |
| 1.4 Emergency telephone number: | +1 703-741-5970 - North America
+1 800-424-9300
+55 11 4349 1359 - South America
+52 55 8526 4930 - Central America
+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa
+65 3163 8374 - Asia, South Asia, And Oceania | | |

2. Hazard Identification

2.1 Classification of the substance or mixture

Carcinogenicity, category 1A
Eye Irritation, category 2A
Flammable Liquid, category 2
Skin Irritation, category 2
Skin Sensitizer, category 1
STOT, single exposure, category 3, RTI

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Methyl methacrylate, Ethylene dimethacrylate, quartz (silicon dioxide), anhydrous aluminum silicate

HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 1A	H350-1A	May cause cancer.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u>	<u>EINEC No.</u>	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>	
limestone	215-279-6	1317-65-3	25 - <50	H315-319	Eye Irrit. 2, Skin Irrit. 2

Methyl methacrylate	201-297-1	80-62-6	25 - <50	H225-315-317-335	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3 RTI
anhydrous aluminum silicate	266-340-9	66402-68-4	2.5 - <10	H315-319-335	Eye Irrit. 2, Skin Irrit. 2, STOT SE 3 RTI
titanium dioxide	236-675-5	13463-67-7	1.0 - <2.5	H351	Carc. 2
Ethylene dimethacrylate	202-617-2	97-90-5	1.0 - <2.5	H317-335	Skin Sens. 1, STOT SE 3 RTI
quartz (silicon dioxide)	238-878-4	14808-60-7	0.1 - <1.0	H350-370	Carc. 1A, STOT SE 1

CAS-No.

1317-65-3
80-62-6
66402-68-4
13463-67-7
97-90-5
14808-60-7

M-Factors

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: No Information

AFTER INHALATION: Move to fresh air. Keep respiratory tract clear.

AFTER SKIN CONTACT: Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Harmful by inhalation. Irritating to eyes. Harmful in contact with skin and if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating may cause an explosion. Flammable. In use, may form flammable/explosive vapour-air mixture.

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Water mist Dry

powder Foam Carbon dioxide (CO₂). Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Take measures to prevent the build up of electrostatic charge. Vapours may form explosive mixtures with air. Provide exhaust ventilation close to floor level. Wear personal protective equipment. Open drum carefully as content may be under pressure. Use only in well-ventilated areas. Keep product and empty container away from heat and sources of ignition. Use only explosion-proof equipment. Have fire extinguishers ready before opening the drum. Do not use sparking tools.

PROTECTION AND HYGIENE MEASURES: Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice for diagnostics.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat. Strong sunlight for prolonged periods.

STORAGE CONDITIONS: Store in original container. Keep in an area equipped with solvent resistant flooring. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

Application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>CAS-No.</u>	<u>ACGIH TWA</u>	<u>ACGIH STEL</u>	<u>ACGIH Ceiling</u>
limestone	1317-65-3	10.00 MG/M3		
Methyl methacrylate	80-62-6	50 PPM	100 PPM	
anhydrous aluminum silicate	66402-68-4	10.0 MG/M3		
titanium dioxide	13463-67-7	10 MGM3	10 MGM3	
Ethylene dimethacrylate	97-90-5			

quartz (silicon dioxide) 14808-60-7 0.025 MGM3

<u>Name</u>	<u>CAS-No.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>
limestone	1317-65-3	5 MGM3 MGM3 15 MGM3 5 MGM3 15 MGM3	
Methyl methacrylate	80-62-6	410 MGM3, 100 PPM	
anhydrous aluminum silicate	66402-68-4	5.0 MG/M3	
titanium dioxide	13463-67-7	15 MGM3	
Ethylene dimethacrylate	97-90-5		
quartz (silicon dioxide)	14808-60-7	0.05 MGM3	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with filter for organic vapor.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Solvent-resistant gloves. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	COLORLESS, CLEAR TO MILKY
Physical State	LIQUID
Odor	STRONG MMA SMELL
Odor threshold	Not determined
pH	NA
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	101 - N.D.
Flash Point, (°F / °C)	52.7F / 11.5C
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	Not determined
Vapour Pressure	@ 68F = 27mmHG (36mbar)
Vapour density	(where air = 1) 4.16
Relative density	Not determined
Solubility in / Miscibility with water	@68f = 16g/l
Partition coefficient: n-octanol/water	Not determined

Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	100-130mPa*s
Explosive properties	Not determined
Oxidising properties	Not determined

9.2 Other information

VOC Content g/l:	20
Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.	
Specific Gravity (g/cm3)	0.989

10. Stability and Reactivity

10.1 Reactivity

Explosive reaction may occur on heating or burning.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat. Strong sunlight for prolonged periods.

10.5 Incompatible materials

Do not store together with oxidizing and self-igniting products.

10.6 Hazardous decomposition products

No Information

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information

Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
80-62-6	Methyl methacrylate	7872 mg/kg (oral, rat)	>5000 mg/kg	3750 ppm (inhalation, rat)	0.000	0.000
13463-67-7	titanium dioxide	10000 mg/kg, oral (rat)			0.000	6,82 mg/l (rat) 4h
97-90-5	Ethylene dimethacrylate	3300 mg/kg, oral, rat			0.000	0.000
14808-60-7	quartz (silicon dioxide)	>2000 mg/kg			0.000	0.000

Additional Information:

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include asbestiform or non-asbestiform tremolite or other silicates as impurities, and above the minimum exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

- 12.1 **Toxicity:**
- | | |
|----------------------|----------------|
| EC50 48hr (Daphnia): | No information |
| IC50 72hr (Algae): | No information |
| LC50 96hr (fish): | No information |
- 12.2 **Persistence and degradability:** No information
- 12.3 **Bioaccumulative potential:** No information
- 12.4 **Mobility in soil:** No information
- 12.5 **Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.
- 12.6 **Other adverse effects:** No information

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
1317-65-3	limestone	No information	No information	
80-62-6	Methyl methacrylate	720 mg/l	No information	125.5 - 275.0 mg/l
66402-68-4	anhydrous aluminum silicate	No information	No information	
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
97-90-5	Ethylene dimethacrylate	No information	No information	
14808-60-7	quartz (silicon dioxide)	No information	No information	

13. Disposal Considerations

- 13.1 **WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. Dispose of as hazardous waste in compliance with local and national regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

14. Transport Information

- 14.1 **UN number** UN1866
- 14.2 **UN proper shipping name** RESIN SOLUTION
- Technical name** Not applicable
- 14.3 **Transport hazard class(es)** 3
- Subsidiary shipping hazard** Not applicable
- 14.4 **Packing group** II
- 14.5 **Environmental hazards** Not applicable
- 14.6 **Special precautions for user** Not applicable
- EmS-No.:** F-E, S-E
- 14.7 **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code** Not applicable

15. Regulatory Information

15.1

Safety, health and environmental regulations/legislation for the substance or mixture:**U.S. Federal Regulations: As follows -****CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>%</u>
Methyl methacrylate	80-62-6	30.07

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
Mequinol	150-76-5

U.S. Clean Air Act:

EPA Coating Category:	INDUSTRIAL MAINTENANCE COATING
EPA VOC Content Limit (g/l):	450
Product VOC Content (g/l)	20
Thinning Recommendations:	The coating is to be applied without thinning.
Application Recommendations:	FOR PROFESSIONAL USE ONLY

* As per the federal EPA definition for coating categories in 40 CFR 59.401.

** Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

U.S. State Regulations: As follows -**New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
acrylic polymer	18275200000-5228
amorphous silica	68611-44-9

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
acrylic polymer	18275200000-5228
amorphous silica	68611-44-9

California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -*** Canadian DSL:**

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H370	Causes damage to organs.

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

- 02 - Hazard Identification
- 03 - Composition/Information On Ingredients
- 09 - Physical and Chemical Properties
- 11 - Toxicological Information
- 15 - Regulatory Information

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m ³	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	International Maritime Organization
Note P:	The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

